


PNP Power Transistor



Features

- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Applications

- Complement to MJD4350
- Signal Amplification

Mechanical Data

- Package: TO-252
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Unit Weight: 0.32g

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Value
Device marking code			MJD5350
Collector-base voltage	V_{CBO}	V	-50
Collector-emitter voltage	V_{CEO}	V	-50
Emitter-base voltage	V_{EBO}	V	-5
Collector current	I_C	A	-3
Power dissipation(*)	P_D	W	2.0
Thermal resistance, junction-to-ambient (*)	R_{thJA}	°C/W	62.5
Junction temperature	T_j	°C	-55 to +150
Storage temperature	T_{STG}	°C	-55 to +150

(*) Device mounted on FR-4 PCB(25.4*25.4*1.0mm)mounting pad.





■ Electrical Characteristics (Ta=25°C unless otherwise noted)






Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=-10mA, I_B=0$	-50		
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=-100\mu A, I_E=0$	-50		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=-100\mu A, I_C=0$	-5		
Collector-base cut-off current	I_{CBO}	nA	$V_{CB}=-50V$			-100
Collector cutoff current	I_{CES}	nA	$V_{CE}=-50V$			-100
Emitter-base cut-off current	I_{EBO}	nA	$V_{EB}=-5V$			-100
DC current gain	h_{FE}		$V_{CE}=-2V, I_C=-500mA$	200		
			$V_{CE}=-2V, I_C=-1A$	200		
			$V_{CE}=-2V, I_C=-2A$	100		
Collector-emitter saturation voltage	$V_{CE(sat)}$	mV	$I_C=-500mA, I_B=-50mA$			-90
			$I_C=-1A, I_B=-50mA$			-180
			$I_C=-2A, I_B=-100mA$			-320
			$I_C=-2A, I_B=-200mA$			-270
			$I_C=-3A, I_B=-300mA$			-390
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	$I_C=-2A, I_B=-100mA$			-1.1
			$I_C=-3A, I_B=-300mA$			-1.2
Base-Emitter Voltage	V_{BE}	V	$V_{CE}=-2V, I_C=-1A$			-1.1
Collector-base output capacitance	C_{ob}	pF	$V_{CB}=-10V, I_E=0A, f=1MHz$		29	

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MJD5350	F1	2500	2500	25000	13"Reel


■ Characteristics(Typical)








■ TO-252 Package information




TO-252		
Dim	Min	Max
A	6.500	6.700
B	5.100	5.460
C	1.400	1.800
D	6.000	6.200
E	10.000	10.400
F	2.166	2.366
G	0.660	0.860
H	Φ 1.050	Φ 1.350
I	0.460	0.580
J	2.200	2.400
K	0	0.300
L	0.890	2.290
M	2.730	3.080
N	0.430	0.580
P	5.15	5.45
Q	0	0.2
R	4.50	5.10
S	1.60	2.40

■ Suggested Pad Layout



Dim	Millimeters
A	11.4
B	6.74
C	6.23
P	4.56
Q1	2.28
Q2	1.52

■ Marking code



Yangjie LOGO
YYWW: YY, years; WW , week.
For example,24 represents 2024; 01 represents the first week of this year.
MJD5350: Product model.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.